

- Easy control of Laser Panel Level (plug-in type)
- It corresponds to 1dB~10dB by using 1dB step
- This product is confirmed and standard (Applicable standard)
- There are always SC/SPC, SC/APC and LC/PC
- RoHS compliant and eco friendly



RoHS compliant products

Product name	Type of connector	Grind method	Return loss	Wavelength	Rated output	Attenuation	Attenuation cross
■ CPJATT-SC/S-□□dB	SC形	SPC研磨 (UPC研磨)	≥ 50dB	SM	1260-1620nm	1W	≤ 0.5dB ※2
■ CPJATT-FC/S-□□dB	FC形						
■ CPJATT-LC/S-□□dB	LC形						
■ CPJATT-MU/S-□□dB	MU形						
■ CPJATT-ST/S-□□dB	ST形						
■ CPJATT-SC/A-□□dB	SC形	APC研磨	≥ 65dB				
■ CPJATT-FC/A-□□dB	FC形						

※1 damping characteristics is differently chosen


※2 The value of attenuation cross of more than 9dB is less than ±10% (10dB, 12dB, 15dB, 20dB, 25dB, 30dB)

※3 SPC grinder is UPC bright dip finished

※4 11dB, 12dB...18dB, 19dB are enable to MTO (Make to Order Manufacturing) separately

Product name

CPJATT-□□/□-□□dB



■ 品名説明

①コネクタ指定

SC FC LC MU ST

②研磨

/S (SPC研磨) /A (APC研磨)

③減衰値

□□dB



各種コネクタに対応しております。



info@encatel.net