



- Used for: F T T H - P O N system and C A T V system
- There are 8 different colors of the code
- It is easy to distinguish the management in order to t
- enable to designate the wavelegth, also you can cutomi about distribution ratio
- It is an International Reliability Test product, corr T e l c o r d i a GR-1209-CORE

Item	Standard value				
Fiber classification	SM (coning SMF-28e 200KPSI)				
Wavelegth area(nm)	1310±20&1490±10&1550±20				
mber of divergence and connec	1×2 divergence				
Diverge ratio	50/50	60/40	70/30	80/20	90/10
he biggest loss in insert(dB)	4.2/4.2	3.3/5.3	2.5/6.6	1.8/8.5	1.2/11.9
PDL(dB)	≤0.3				
Return loss (dB)	≥55				
e of the part of divergence (W20×L90×H10				

Product name

ATC3W1×2 - 50/50 - SC/S (Lm·YL) - SC/S(L1m·YL) *2 -TS

divergence rate	connector and length of diverge code	code color	The colors which fit with the codes
50/50	SC/S Lm Input length・**	BL	※指示なき場合の標準色
60/40	SC/A L1m Input length・**	YL	
70/30	FC/S	GR	
80/20	.	RD	
90/10	.	VI	
	.	WH	
	.	BR	
	.	BK	